

**CD1 Electric Hoist**

CD1 electric hoist electric hoist is a small lifting equipment, which can be installed on single girder, double girder, bridge crane, gantry crane, and other multiple cranes. The lifting speed is constant speed, which can meet the needs of general occasions. , one of the commonly used lifting equipment in ports, warehouses and freight yards, which can improve labor efficiency and improve labor conditions

Advantage

1. Anti-stripping drum, double flange: it is characterized in that the flange of the reducer and the flange of the motor corresponding to the outer wall of the two ends of the drum are respectively provided with a ring of abrupt platform, the clearance between the abrupt platform and the drum is less than the diameter of a traction ropeEasy operating need no training
2. Special motor does not contain asbestos and is better waterproof.
3. 2.0 manganese steel hook imported Schneider Electric .
4. The rope guide is thickened and widened

Electric wire hoist is a kind of small lifting equipment. It can mounted on single beam overhead cranes. Gantry cranes CD1 electric hoist type electric wire hoist as only one normal speed which can satisfy normal application . It is widely used in factories, mines, warehouse cargo storage and shops. CD1 electric hoist type electric wire hoist can raising working efficiency and improving working conditions.

Product Parameter (Specification)

Model	0.5T	1T	2T	3T	5T	10T
Capacity	0.5	1	2	3	5	10
Lifting Height	6-12	6-30	6-30	6-30	6-30	9-30
Lifting speed	8.8/0.8	8.8/0.8	8.8/0.8	8.8/0.8	8.8/0.8	7.7/0.7
Moving speed	20(30)	20(30)	20(30)	20(30)	20(30)	20(30)
Model of wire rope	6*37-4.8-180	6*37-7.4-180	6*37-11-155	6*37-13-170	6*37-15-200	6*37-17.5-5200
I-beam track model	16-28b	16-28b	20s-32c	20a-32c	25a-63c	28a-63c
Operating voltage	3-Phase 220V-690V 50/60HZ					

Product Feature And Application**Product Details**

1. Anti-stripping drum, double flange: it is characterized in that the flange of the reducer and the flange of the motor corresponding to the outer wall of the two ends of the drum are respectively provided with a ring of abrupt platform, the clearance between the abrupt platform and the drum is less than the diameter of a traction rope.

PRODUCT ADVANTAGES

quality is everything

MOTOR

our supplier brand is Nanjing motor, Nanjing special motor etc, or as your requirement



2. Special motor does not contain asbestos and is better waterproof

GEAR BOX

Gear box using for hoist lifting,
Adopt round and square gear box,
Choose the type according to your
needs



3. Tianzheng Electric, contactor brand: Daryl (Yueqing Daryl Electric Factory) imported Schneider Electric

HOOK

European style hook, with 360 degree rotation and height bearing strength



4. 2.0 manganese steel hook2.0

ROPE GUIDE

prevent the wire rope from winding disorderly, Support customized widening Thicken



5. The rope guide is thickened and widened

6. The outer housing is thickened steel plate

WIRE ROPE

Bold solid steel wire rope, hemp core material, heavy load-bearing, not easy to break

Product Qualification

Founded in 2002, Shanghai Yiyong Lifting Co., Ltd. is a powerful enterprise integrating R&D, production and sales of high-end lifting equipment and is committed to providing handling and lifting solutions for global customers. The company's products have obtained CE, TUV, and many other export quality certifications, and 7 patent protections, winning the love and trust of new and old customers. We adhere to customer-centricity, adhere to quality assurance, and be a powerful enterprise.

Deliver,Shipping And Serving

Pre-sale Services : Provide customers with relevant information of Diniu, guide you to choose the correct model and provide accurate answers, assist customers in planning and demand analysis, so that our products can meet the needs of users to the greatest extent.

Sale services: Special personnel provide services. From the moment consumers place an order, our sales team has been tracking from procurement, processing, freight forwarding, and receipt, and timely feedback.

After-sale services :The company provides consumers with a series of after-sales services, including product introduction, transportation, installation guidance, debugging, and the after-sales team will handle all complaints from customers.

Delivery time: 3-5 days within 10 pieces

10-15days 15-20pcs

20+ 20+pcs

FAQ

1. What is the CD1 electric hoist protection level CD1 electric hoist

IP44

2. What is the general level of work

M3

3. CD1 electric hoist 2T6M lift speed 3 running speed 5 can do how to achieve

Yes, by frequency conversion (lifting motor plus a frequency conversion, set the speed as 3, running motor plus a frequency conversion, set the speed as 5)

4. How long is the warranty

Quality assurance 1 year

5. Does CD1 electric hoist use oil before use? What kind of oil?

To add oil, add liquid gear oil and 17-500ml.

Detailed refueling instructions are given on page 14 of the manual